

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

A pine snag, 10 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ W.,
138 lks. dist., mkd. with visible scribe mks. on
a rotting face. (Record bearing, N. 75° W.)

bearing trees mkd. by Byron:

A fir, 15 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ E., $16\frac{1}{2}$ lks.
dist., mkd. T31S R7W S34 CS BT on a double
blaze.

A pine, 17 ins. diam., bears N. 71° W., 74 lks.
dist., mkd. with a partially healed double
blaze.

and a new bearing tree,

A cedar, 19 ins. diam., bears N. 52° E., 11 lks.
dist., mkd. T31S R7W S27 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, hemlock, madrone, maple, yew,
chinquapin, live oak, cedar, and dogwood; undergrowth,
salal, young timber, live oak, huckleberry, arrowwood,
hazel, vine maple, rhododendron, Oregon grape, ferns,
and vines.

From the cor. of secs. 26, 27, 34, and 35.

S. $89^{\circ} 33'$ W., bet. secs. 27 and 34.

Descend 310 ft. over NW. slope, through heavy timber
and thin undergrowth.

9.05 Cedar Creek, 7 lks. wide, course S. 20° W.; asc. 110 ft.
over E. slope.

9.70 Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.

11.20 Top of rock bluff, 80 ft. high; edge bears N. and S.;
asc. 165 ft. over E. slope.

25.75 Spur, slopes S. 20° W.; desc. 45 ft. over SW. slope.

30.70 Wet draw, drains S.; asc. 65 ft. over SE. slope.

40.05 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, recorded and re-
monumented in 1962 by Howard W. Johnstone, Registered
Land Surveyor No. 498, with a wooden stake, 6 ft. long,
2 ins. square, firmly set 12 ins. in the ground, from
which the remains of the original bearing trees:

A pine snag, 35 ins. diam., bears N. 5° W., 69 lks
dist., with no mks. visible.

A down pine, 14 ins. diam., bears S. 70° W., 21
lks. dist., with illegible scribe mks. visible
on opened and burned double blaze.

and bearing trees mkd. by Johnstone:

A fir, 8 ins. diam., bears N. 45° W., 13 lks.
dist., mkd. with a partially healed double
blaze.

A pine, 35 ins. diam., bears S. 87° E., 83 lks.
dist., mkd. with a partially healed blaze.

At the corner point