

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
 $\frac{1}{4}$ S 27
S 34
1964

S. $89^{\circ} 16'$ W., beginning new measurement.

Ascend 30 ft. over SE. slope.

- 7.30 Spur, slopes S. 40° W.; desc. 175 ft. over W. slope.
- 12.05 Creek, 4 lks. wide, course S. 25° W.; asc. 215 ft. over SE. slope.
- 23.00 Spur, slopes S.; desc. 20 ft. over SW. slope.
- 26.25 Creek, 2 lks. wide, course S. 15° E.; asc. 165 ft. over SE. slope.
- 37.35 Top of ascent, slopes S.; desc. 20 ft. along S. slope.
- 39.90 The cor. of secs. 27, 28, 33, and 34.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, hemlock, cedar, dogwood, maple, madrone, yew, chinquapin, and alder; undergrowth, salal, huckleberry, Oregon grape, poison oak, young timber, live oak, manzanita, arrowwood, hazel, vines, and ferns.

N. $0^{\circ} 07'$ W., bet. secs. 27 and 28.

Ascend 290 ft. over S. slope, through heavy timber and thin undergrowth.

- 17.75 Spur, slopes SE.; asc. 5 ft. along E. slope, changing to SE. slope.
- 20.00 Point for the S $\frac{1}{16}$ sec. cor. of secs. 27 and 28.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

S $\frac{1}{16}$
S 28 | S 27
1964

from which

A fir, 12 ins. diam., bears S. $19\frac{1}{4}^{\circ}$ E., 65 lks. dist., mkd. S $\frac{1}{16}$ S27 BT.

A fir, 25 ins. diam., bears S. $26\frac{1}{4}^{\circ}$ W., 48 lks. dist., mkd. S $\frac{1}{16}$ S28 BT.

Ascend 225 ft. over SE. slope.

- 28.90 Enter meadow; edge bears E. and W.
- 33.70 Leave meadow; enter heavy timber; edge bears E. and W.