

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS 33.70	Leave meadow; enter heavy timber; edge bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 31 S R 7 W S 28 $\frac{1}{4}$ S 27 1964 from which A fir, 20 ins. diam., bears N. 67° E., 19 lks. dist., mkd. $\frac{1}{4}$ S27 BT. A fir, 13 ins. diam., bears S. 51° W., 70 lks. dist., mkd. $\frac{1}{4}$ S28 BT. Corner is on top of spur, slopes S. 20° W.; desc. 110 ft. along W. slope.
51.20	Draw, drains S. 70° W.; asc. 130 ft. over broken SW. slope.
60.00	Point for the N $1/16$ sec. cor. of secs. 27 and 28. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. N $1/16$ S 28 S 27 1964 from which A fir, 15 ins. diam., bears N. $83\frac{3}{4}^\circ$ E., 104 lks. dist., mkd. N $1/16$ S27 BT. A fir, 9 ins. diam., bears N. 24° W., 112 lks. dist., mkd. N $1/16$ S28 BT. Corner is on top of spur, slopes W.; desc. 150 ft. over NW. slope.
65.70	Wet draw, drains N. 45° W.; desc. 230 ft. over NW. slope.
80.00	Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd. T 31 S R 7 W S 21 S 22 S 28 S 27 1964 from which A fir, 9 ins. diam., bears N. 59° E., 23 lks. dist., mkd. T31S R7W S22 BT.