

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 31 S., R. 7 W.

CHAINS	
	<p>A fir, 15 ins. diam., bears S. 76° E., 200 lks. dist., mkd. T31S R7W S27 BT.</p> <p>A fir, 15 ins. diam., bears S. 18½° W., 214 lks. dist., mkd. T31S R7W S28 BT.</p> <p>A fir, 15 ins. diam., bears N. 81° W., 29 lks. dist., mkd. T31S R7W S21 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, pine, fir, hemlock, cedar, madrone, and chinquapin; undergrowth, salal, young fir, Oregon grape, poison oak, arrowwood, vines, and ferns.</p>
	<p>From the cor. of secs. 22, 23, 26, and 27. S. 89° 49' W., bet. secs. 22 and 27. Ascend 35 ft. over SE. slope, through heavy timber and thin undergrowth.</p>
2.50	Spur, slopes S.; desc. 175 ft. over SW. slope.
10.10	Creek 1 lk. wide, course S.; asc. 100 ft. over SE. slope.
14.10	Spur, slopes S.; desc. 35 ft. over SW. slope.
17.75	Wet draw, drains S.; asc. 230 ft. over SE. slope.
36.10	Ridge and dirt road, N. 55° E., and S. 55° W.; desc. 50 ft. over NW. slope.
39.92	<p>The ¼ sec. cor. of secs. 22 and 27, recorded and re-monumented in 1962 by Howard W. Johnstone, Registered Land Surveyor No. 498, with an iron pipe, 1 in. diam., 6 ins. above ground, firmly set, from which the original bearing trees:</p> <p>A fir, 71 ins. diam., bears N. 54° E., 35 lks. dist., (31 lks. to face), mkd. ¼ S T on a bark blaze. (Record distance, 31 lks.)</p> <p>A fir, 48 ins. diam., bears S. 16° W., 24 lks. dist., with no mks. visible.</p> <p>and bearing trees mkd. by Johnstone:</p> <p>A fir, 21 ins. diam., bears N. 24° W., 96 lks. dist., mkd. with a partially healed double blaze.</p> <p>A fir, 12 ins. diam., bears S. 62½° W., 43 lks. dist., mkd. with a partially healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 31 S R 7 W ¼ S 22 ¼ S 27 1964</p>