

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 32 | S 33
1964

from which

A fir, 35 ins. diam., bears N. 31° E., 63 lks. dist., mkd. S 1/16 S33 BT.

A fir, 15 ins. diam., bears N. $17\frac{1}{4}^\circ$ W., 94 lks. dist., mkd. S 1/16 S32 BT.

Ascend 80 ft. over SW. slope.

27.20 Spur, slopes W.; desc. 270 ft. over N. slope, changing to NE. slope.

34.65 Creek, 1 lk. wide, course NW.; asc. 5 ft. over SW. slope.

36.75 Top of ascent, slopes W.; desc. 130 ft. over NW. slope.

41.76 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, determined at record distance from the remains of the original bearing trees:

A stump hole, bears N. 87° E., 45 lks. dist.; found madrone snag, 12 ins. diam., lying down hill from the stump hole, no mks. remaining on rotted face. (Record bearing, South)

A fir, 50 ins. diam., bears West, 37 lks. dist., mkd. $\frac{1}{4}$ S BT on bark blaze, on East side of tree. (Record bearing, N. 3° W.)

The corner falls on a blazed line which extends north and south.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33
T 31 S R 7 W
1963

from which a new bearing tree

A fir, 15 ins. diam., bears N. $57\frac{3}{4}^\circ$ E., 77 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

N. $0^\circ 18'$ E., beginning new measurement.

Descend 325 ft. over NW. slope.

13.70 Middle Creek, 35 lks. wide, course S. 30° W.; asc. 350 ft. over SE. slope.

14.90 Middle Creek Road, 40 lks. wide, bears N. 55° E. and S. 30° W., on curve.