

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS	
27.95	Spur, slopes SE.; desc. 15 ft. over NE. slope.
30.40	Creek, 1 lk. wide, course SE.; asc. 265 ft. over SW. slope.
39.73	Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 31 S R 7 W S 29 S 28 S 32 S 33 1963
	from which
	A fir, 24 ins. diam., bears N. 83° E., 53 lks. dist., mkd. T31S R7W S28 BT.
	A cedar, 32 ins. diam., bears S. 71° E., 67 lks. dist., mkd. T31S R7W S33 BT.
	A fir, 15 ins. diam., bears S. 80° W., 130 lks. dist., mkd. T31S R7W S32 BT.
	A fir, 20 ins. diam., bears N. 30° W., 46 lks. dist., mkd. T31S R7W S29 BT.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, hemlock, live oak, madrone, chinquapin, yew, maple, and dogwood; undergrowth, hazel, huckleberry, salal, live oak, poison oak, manzanita, Oregon grape, arrowwood, vine maple, young timber, vines, and ferns.
	From the cor. of secs. 27, 28, 33, and 34.
	S. 89° 29' W., bet. secs. 28 and 33.
	Descend 65 ft. over S. slope, changing to SE. slope, through heavy timber and dense undergrowth.
5.65	Creek, 1 lk. wide, course S.; asc. 45 ft. over SE. slope.
11.00	Top of ascent, slopes S.; desc. 50 ft. over broken SW. slope.
18.15	Wet draw, drains S. 35° W.; asc. 45 ft. over SE. slope.
27.10	Spur, slopes S. 20° W.; desc. 30 ft. over SW. slope.
37.15	Spur, slopes S.; desc. 85 ft. over W. slope.
40.31	The ¼ sec. cor. of secs. 28 and 33, determined at record bearing and distance from the original bearing trees:
	A fir, 48 ins. diam., bears N. 62° E., 56 lks. dist. (53 lks. to face), mkd. ¼ S BT on bark blaze. (Record distance, 53 lks.)