

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

A fir, 33 ins. diam., bears S. 31° W., 42 lks. dist. (40 lks. to face), mkd. $\frac{1}{4}$ S BT on bark blaze. (Record distance, 40 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 28}{S \ 33}$$

T 31 S R 7 W
1963

N. 89° 45' W., beginning new measurement.

Descend 390 ft. over W. slope.

- 9.60 Creek, 8 lks. wide, course S.; asc. 350 ft. over E. slope.
- 26.05 Spur, slopes S. 30° E.; desc. 5 ft. over SW. slope.
- 34.15 Draw, drains S.; asc. 45 ft. over E. slope.
- 38.10 Spur, slopes S.; desc. 5 ft. over SW. slope.
- 39.88 The cor. of secs. 28, 29, 32, and 33.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, live oak, madrone, hemlock, chinquapin, maple, and yew; undergrowth, young timber, manzanita, huckleberry, arrowwood, vine maple, poison oak, salal, Oregon grape, live oak, vines, and ferns.

N. 0° 18' W., bet. secs. 28 and 29.

Ascend 195 ft. over SW. slope, changing to S. slope, through heavy timber and light undergrowth.

- 14.20 Spur, slopes S. 40° E.; desc. 55 ft. over NE. slope.
- 20.80 Draw, drains SE.; asc. 100 ft. over SW. slope.
- 28.30 Spur, slopes S. 75° E.; desc. 45 ft. over NE. slope.
- 33.25 Creek, 1 lk. wide, course E.; asc. 100 ft. over S. slope, changing to SE. slope.
- 39.73 The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, determined at record distance from the remains of the original bearing trees:

A pine, 55 ins. diam., bears S. 29° E., 168 lks. dist., no mks. visible on bark blaze.

A pine snag, 33 ins. diam., bears N. 89° W., 159 lks. dist., mkd. $\frac{1}{4}$ S on open blaze. (Record bearing, S. 84° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.