

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \text{ | } \text{S } 28 \\ \text{T } 31 \text{ S | R } 7 \text{ W} \\ 1963 \end{array}$$

from which new bearing trees

A fir, 11 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ E., 38 lks.
dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 14 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., $48\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S29 BT.

N. $0^{\circ} 13'$ W., beginning new measurement.

Ascend 80 ft. over SE. slope.

- 6.80 Trail, bears N. 70° W. and S. 70° E.
- 12.10 Spur, slopes S. 65° E.; desc. 125 ft. over NE. slope.
- 18.75 Creek, 1 lk. wide, course S. 80° E.; asc. 140 ft. over S. slope.
- 24.65 Spur, slopes SE.; desc. 90 ft. over NE. slope.
- 27.55 Wet draw, drains S. 80° E.; asc. 280 ft. over E. slope, changing to SE. slope.
- 39.65 The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the remains of the original bearing trees:
- A pine snag, 60 ins. diam., bears N. 10° E., 18 lks. dist., no mks. visible.
- A stump hole, bears S. 5° E., 29 lks. dist.
- A cedar, 30 ins. diam., bears N. 57° W., 8 lks. dist., mkd. with old axe mks. on open, burned blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 31 \text{ S } \text{R } 7 \text{ W} \\ \text{S } 20 \text{ | } \text{S } 21 \\ \text{S } 29 \text{ | } \text{S } 28 \\ 1963 \end{array}$$

from which new bearing trees

A fir, 10 ins. diam., bears N. $38\frac{3}{4}^{\circ}$ E., 66 lks.
dist., mkd. T31S R7W S21 BT.

A fir, 6 ins. diam., bears S. 5° E., 53 lks.
dist., mkd. T31S R7W S28 BT.

A fir, 15 ins. diam., bears S. $16\frac{1}{2}^{\circ}$ W., 53 lks.
dist., mkd. T31S R7W S29 BT.

A fir, 9 ins. diam., bears N. $35\frac{3}{4}^{\circ}$ W., 50 lks.
dist., mkd. T31S R7W S20 BT.