

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 31 S., R. 7 W.

## CHAINS

7.00	Creek, 2 lks. wide, course S. 30° E.; asc. 155 ft. over NE. slope.
15.65	Spur, slopes SE.; asc. 215 ft. over SE. slope.
33.10	Creek, 1 lk. wide, course S. 45° E.; asc. 250 ft. over NE. slope.
39.97	The cor. of secs. 20, 21, 28, and 29.  Land, mountainous. Soil, rocky clay. Timber, pine, fir, hemlock, cedar, maple, madrone, chinquapin, yew, and dogwood; undergrowth, salal, Oregon grape, arrowwood, vine maple, hazel, live oak, huckleberry, poison oak, ferns, and vines.
	From the cor. of secs. 28, 29, 32, and 33.  S. 89° 11' W., bet. secs. 29 and 32.  Descend 30 ft. over SW. slope, through heavy timber and thin undergrowth.
2.20	Draw, drains S.; asc. 65 ft. over SE. slope.
10.55	Wet draw, drains SE.; asc. 60 ft. over broken SE. slope.
15.70	Creek, 3 lks. wide, course SE.; asc. 245 ft. over broken SE. slope.
37.90	Ridge, bears N. 30° E. and S. 30° W.; desc. 35 ft. over W. slope.
39.89	The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, determined at record bearing and distance from the remains of the original bearing trees:  A madrone, 20 ins. diam., bears N. 23° W., 27 lks. dist., mkd. $\frac{1}{4}$ S on open blaze.  A rotted pine stump, 30 ins. diam., bears S. 40° E., 11 lks. dist., with no mks. remaining.  At the corner point  Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \text{ S } 29 \\ \frac{1}{4} \text{ S } 32 \\ \text{T 31 S R 7 W} \\ 1963 \end{array}$  from which new bearing trees  A fir, 6 ins. diam., bears N. 30 $\frac{1}{2}$ ° E., 25 lks. dist., mkd. $\frac{1}{4}$ S29 BT.  A fir, 8 ins. diam., bears S. 10 $\frac{1}{2}$ ° W., 19 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S32 BT.  <hr/> N. 89° 14' W., beginning new measurement.  Descend 185 ft. over W. slope.