

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

- 39.00 Creek, 2 lks. wide, course N.; asc. 30 ft. over NE. slope.
- 40.17 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, determined at record bearing and distance from the original NE. bearing tree and record bearing from the original SW. bearing tree:
- A fir, 53 ins. diam., bears N. 39° E., 27 lks. dist., with partial scribe mks. visible on bark blaze.
- A fir, 70 ins. diam., bears S. 24° W., 96 $\frac{1}{2}$ lks. dist., with scribe mks. $\frac{1}{4}$ S visible on bark blaze. (Record distance, 42 lks.)
- At the corner point
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\frac{1}{4} \frac{S \ 20}{S \ 29}$$

T 31 S R 7 W
1963
- from which new bearing trees
- A fir, 18 ins. diam., bears N. 2° W., 67 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S20 BT.
- A fir, 12 ins. diam., bears S. 66 $\frac{3}{4}$ ° E., 79 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
-
- S. 89° 19' W., beginning new measurement.
- Ascend 180 ft. over E. slope, through heavy timber and dense undergrowth.
- 6.75 Spur, slopes N. 20° E.; desc. 330 ft. over NW. slope.
- 22.00 Head of draw, drains N. 30° W.; asc. 10 ft. over NE. slope.
- 23.60 Spur, slopes N. 35° W.; desc. 365 ft. over SW. slope, changing to S. slope.
- 39.07 The cor. of secs. 19, 20, 29, and 30, determined from the original bearing trees:
- A fir, 21 ins. diam., bears N. 56° E., 58 lks. dist., with scribe mks. W BT visible on bark blaze. (Record bearing, N. 53° E.)
- A fir, 25 ins. diam., bears S. 76 $\frac{1}{2}$ ° E., 50 lks. dist., with scribe mks. T S BT visible on bark blaze. (Record bearing, S. 78° E.)
- A madrone snag, 17 ins. diam., bears S. 8° W., 41 lks. dist., with illegible scribe mks. visible on rotted blaze. (Record distance, 25 lks.)
- A fir, 35 ins. diam., bears N. 8° W., 70 lks. dist., with illegible scribe mks. visible. (Record bearing, N. 14° W.)