

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,
T. 31 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
S 19 | S 20
S 30 | S 29
1963

from which new bearing trees

A fir, 10 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. T31S R7W S30 BT.

A fir, 7 ins. diam., bears N. $19\frac{1}{2}^{\circ}$ W., 27 lks. dist., mkd. T31S R7W S19 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, live oak, madrone, chinquapin, and yew; undergrowth, young timber, manzanita, huckleberry, salal, hazel, arrowwood, vine maple, poison oak, live oak, Oregon grape, vines, and ferns.

The following subdivision of sections 27 and 35 was executed in conformity with legal surveying practice. The record of true line notes, only, is set forth in the following field notes.

Subdivision of Sec. 35, T. 31 S., R. 7 W.

From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.

N. $0^{\circ} 09'$ E., on the N. and S. center line of sec. 35, marking and blazing the true line.

Ascend 160 ft. over SW. slope, through heavy timber and thin undergrowth.

8.15 Ridge, bears NW. and SE.; desc. 150 ft. over NE. slope.

23.40 Bottom of descent, slopes E.; asc. 40 ft. over SE. slope.

32.90 Spur, slopes NE.; desc. 235 ft. over NE. slope, changing to N. slope.

39.585 Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$C\frac{1}{4}$ S 35
1964

from which

A fir, 26 ins. diam., bears N. 34° E., 65 lks. dist., mkd. $C\frac{1}{4}$ S35 BT.