

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of Sec. 35, T. 31 S., R. 7 W.

CHAINS	
	A fir, 21 ins. diam., bears S. 53° W., 25 lks. dist., mkd. C $\frac{1}{4}$ S35 BT.
	Descend 55 ft. over NE. slope.
42.00	Spur, slopes N. 20° E.; desc. 390 ft. over NW. slope.
57.35	Middle Creek Road, 25 lks. wide, bears N. 20° E. and S. 20° W.
61.80	Middle Creek, 25 lks. wide, course S. 25° W.; asc. 130 ft. over SE. slope.
70.75	Creek, 1 lk. wide, course S. 20° E.; asc. 80 ft. over SW. slope.
71.45	Dirt road, 15 lks. wide, bears N. 65° E. and S. 65° W.
77.20	Creek, 1 lk. wide, course S. 30° W.; asc. 60 ft. over SE. slope.
79.75	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
	From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.
	S. 89° 21' W., on the E. and W. center line of sec. 35.
	Descend 5 ft. over NW. slope, through heavy timber and thin undergrowth.
2.20	Draw, drains S. 70° W.; desc. 105 ft. over SW. slope.
8.45	Blazed trail, bears N. and S.
11.80	Martin Creek, 15 lks. wide, course N. 20° W.; asc. 230 ft. over E. slope, changing to SE. slope.
19.945	Point for the center E 1/16 sec. cor. of sec. 35.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \quad \text{E } 1/16 \\ \quad \quad \text{S } 35 \\ \quad \quad \quad \text{C} \\ \quad \quad \quad 1964 \end{array}$
	from which
	A fir, 10 ins. diam., bears N. 53 $\frac{3}{4}$ ° E., 93 lks. dist., mkd. CE 1/16 S35 BT.
	A fir, 20 ins. diam., bears S. 4° W., 47 lks. dist., mkd. CE 1/16 S35 BT.
	Ascend 240 ft. over SE. slope.
29.70	Spur, slopes N. 35° E.; desc. 140 ft. over NW. slope.
36.55	Draw, drains N.; asc. 65 ft. over NE. slope.
39.89	The center $\frac{1}{4}$ sec. cor. of sec. 35.
	Ascend 30 ft. over NE. slope.
42.90	Spur, slopes N. 30° W.; desc. 130 ft. over NW. slope.