

12646 County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 35, T. 31 S., R. 7 W.

CHAINS

- 47.15 Draw, drains NW.; asc. 15 ft. over NE. slope.
- 51.50 Spur, slopes N. 50° W.; desc. 220 ft. over SW. slope.
- 61.70 Draw, drains N. 85° W.; desc. 130 ft. over NW. slope.
- 73.55 Buck Creek, 12 lks. wide, course N. 30° E.; asc. 205 ft. over E. slope.
- 77.30 Dirt Road, 15 lks. wide, bears N. 20° E. and S. 20° W.
- 79.88 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

From the center E 1/16 sec. cor. of sec. 35.

N. 0° 08' E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 35.

Ascend 5 ft. over SE. slope, through heavy timber and thin undergrowth.

- 0.45 Spur, slopes E.; desc. 260 ft. over NE. slope.
- 19.00 Martin Creek, 12 lks. wide, course N. 80° W.; asc. 20 ft. over S. slope.
- 19.75 Spur, slopes N. 80° W.; desc. 25 ft. over NW. slope.
- 21.10 Middle Creek, 15 lks. wide, course S. 75° W.; asc. 225 ft. over SE. slope.
- 22.15 Middle Creek Road, 25 lks. wide, bears N. 75° E. and S. 75° W.
- 31.95 Dirt road, 15 lks. wide, bears NE. and S. 70° W.
- 40.05 The E 1/16 sec. cor. of secs. 26 and 35.

Subdivision of Sec. 27, T. 31 S., R. 7 W.


From the $\frac{1}{4}$ sec. cor. of sec. 27 and 34.

N. 0° 01' E., on the N. and S. center line of sec. 27.

Ascend 205 ft. over SE. slope, through heavy timber and dense undergrowth.

- 12.30 Spur, slopes SW.; desc. 75 ft. over NW. slope.
- 19.97 Point for the center S 1/16 sec. cor. of sec. 27.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 8 ins. diam., bears N. 36° E., 48 lks. dist., mkd. CS 1/16 S27 BT.