

County Surveyor's Record, Douglas County, Oregon

T. 32 S., R. 7 W.

CHAINS

The history of surveys in that portion of T. 32 S., R. 7 W., Willamette Meridian, Oregon, covered by this resurvey is as follows:

The subdivisional lines were surveyed by William H. Byars in 1881. The N. bdy. of sec. 3 was resurveyed concurrently with the resurveys in T. 31 S., R. 7 W.

The resurvey was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey are retraced and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions, lost corners are reestablished and remonumented at proportionate positions, based on the original record. The retracement data are thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing, public lands are blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 25, 1964, under Group 543.

The directions of the lines were determined by the solar transit method.

The geographic position of the southeast corner of section 3, as scaled from the Dutchman Butte Quadrangle map, prepared by the United States Geological Survey, in 1946, is as follows:

Latitude $42^{\circ} 48.7' N.$ Longitude $123^{\circ} 30.3' W.$

The mean magnetic declination is $19^{\circ} 30' E.$

Dependent Resurvey of a Portion of the
Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon
(Restoring the 1881 survey by William H. Byars)

The cor. of secs. 2, 3, 10, and 11, monumented with the original corner tree, a fir, 12 ins. diam., mkd. with healed blazes on the NE., SE., SW. and NW. sides, from which the original bearing trees:

A fir, 44 ins. diam., bears N. $62^{\circ} E.$, 90 lks. dist., mkd. T32S R7W S2 BT on bark blaze. (Record, 97 lks.)

A fir, 53 ins. diam., bears S. $16^{\circ} E.$, 50 lks. dist., with illegible scribe mks. on bark blaze. (Record, S. $22^{\circ} E.$, 46 lks.)

A fir, 55 ins. diam., bears S. $38^{\circ} W.$, 94 lks. dist., mkd. T32S R7W S10 BT on bark blaze. (Record 89 lks.)

A fir, 34 ins. diam., bears N. $25^{\circ} W.$, 70 lks. dist., mkd. T2S R7W S3 BT on bark blaze. (Record, N. $35^{\circ} W.$, 68 lks.)