

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W.

| CHAINS | |
|--------|--|
| | <p>add a new bearing tree and reference monument</p> <p>A fir, 15 ins. diam., bears S. 65° E., 74 lks. dist., mkd. T32S R7W S11 BT.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 62° E., 19½ lks. dist., with brass cap mkd. T32S R7W S2 RM 1964 and an arrow pointing to the corner.</p> <p>The corner falls on spur, slopes S. 80° E.</p> <p>N. 1° 27' W., bet. secs. 2 and 3, marking and blazing true line.</p> <p>Descend 20 ft. over NE. slope, through heavy timber and light undergrowth.</p> |
| 2.50 | Ravine, drains S. 80° E.; asc. 440 ft. over broken SE. slope. |
| 32.60 | Spur, slopes N. 80° E.; desc. 250 ft. over N. slope, changing to NE. slope. |
| 40.61 | <p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W</p> <p>S 3 S 2</p> <p>1964</p> </div> <p>from which</p> <p>A fir, 6 ins. diam., bears S. 23° E., 81 lks. dist., mkd. ¼ S2 BT.</p> <p>A fir, 6 ins. diam., bears N. 45° W., 55 lks. dist., mkd. ¼ S3 BT.</p> <p>Descend 100 ft. over NE. slope.</p> |
| 47.55 | Ravine, drains E.; asc. 15 ft. over SE. slope. |
| 48.60 | Spur, slopes N. 50° E.; desc. 390 ft. over NW. slope. |
| 60.20 | Creek, 6 lks. wide, course N. 85° E.; asc. 40 ft. over SE. slope. |
| 62.90 | Spur, slopes SE.; desc. 10 ft. over NE. slope. |
| 63.30 | Creek, 1 lk. wide, course S. 65° E.; asc. 45 ft. over SE. slope. |
| 65.55 | Spur, slopes S. 75° E.; desc. 15 ft. over NE. slope. |
| 68.50 | Ravine, drains S. 55° E.; asc. 80 ft. over S. slope, changing to SE. slope. |
| 72.20 | Dirt road, 15 lks. wide, bears N. 60° E. and S. 80° W. |
| 76.45 | Spur, slopes E., also trail bears E. and W., along top of spur; desc. 55 ft. over NE. slope. |