

## County Surveyor's Record, Douglas County, Oregon

T. 21 S., R. 8 W., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of an original corner point in Township 21 South, Range 8 West, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".

(Remonumentation of a corner established in 1883 by William P. Wright and remonumented in 1945 by Norman D. Price and George F. Rigby.)

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, determined at record bearing distance from the 1883 bearing trees:

A down fir, 25 ins. diam., bears N.  $54^{\circ}$  E., 23 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on opened blaze.

A fir, 14 ins. diam., bears N.  $85^{\circ}$  W., 45 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partially healed blaze.

and 1945 bearing trees

A fir, 33 ins. diam., bears S.  $20^{\circ}$  E., 59 lks. dist., with a healed blaze.

A fir, 41 ins. diam., bears N.  $89^{\circ}$  W., 67 lks. dist., with a healed blaze.

The 1945 iron post is lost.

At the corner Point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S R 8 W

S 9 } S 10  
1963

FD. OK 10/67  
D. BAKER  
M 97-51

from which a new bearing tree

A hemlock, 23 ins. diam., bears N.  $72\frac{3}{4}^{\circ}$  E., 122 lks. dist., mkd.  $\frac{1}{4}$  S10 BT.