

County Surveyor's Record, Douglas County, Oregon

T. 32 S., R. 8 W.

CHAINS

The following is the remonumentation of certain original corner points in township 32 south, range 8 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Groupd No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".

The remonumentation of the original corner points was made at the request of the Medford District Manager for administrative purposes of the Bureau of Land Management.

(Remonumenting the Corner Established by W. H. Byars, 1881)

The cor. of secs. 13, 18, 19 and 24, on the E. bdy, of the Tp., determined at record bearing and distance from three remaining original bearing trees:

A madrone, 16 ins. diam., bears N. 30° E., 81 lks. dist., no marks remaining on opened blaze.

A fir, 24 ins. diam., bears S. 55° W., 23 lks. dist., with illegible scribe marks visible on an opened and burned blaze.

A live oak, 12 ins. diam., bears N. 55° W., 81 lks. dist., with scribe marks R8W S13 visible on opened blaze.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T 32 S	
R 8 W	R 7 W
S 13	S 18
S 24	S 19
1958	

from which

A fir, 18 ins. diam., bears N. 19° E., 85 lks. dist., mkd. T32S R7W S18 BT.

A fir, 9 ins. diam., bears S. 70½° E., 54 lks. dist., mkd. T32S R7W S19 BT.

A fir, 14 ins. diam., bears S. 72½° W., 75 lks. dist., mkd. T32S R8W S24 BT.

A fir, 12 ins. diam., bears N. 74° W., 47 lks. dist., mkd. T32S R8W S13 BT.

(Remonumenting the Corner Established by R. S. Dickerson, 1883)

The cor. of secs. 20, 21, 28 and 29, determined at record distance from the two remaining original bearing trees:

A fir, 23 ins. diam., bears N. 5° E., 23 lks. dist., bark scribed T32S R8W S20 BT. (Record bearing, N. 5° W.) Rescribe this tree T32SR8W S21 BT below the other marks.

A fir, 24 ins. diam., bears S. 70° W., 58 lks. dist., bark scribed T32S R8W S29 BT.