

County Surveyor's Record, Douglas County, Oregon

T. 22 S., R. 9 W.

CHAINS

The following field notes describe the remonumentation of the $\frac{1}{4}$ section corner of sections 13 and 24, township 22 south, range 9 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Groupd No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Point, With New Accessories When Needed".

The remonumentation of the corner was made at the request of the Coos Bay District Manager, for administrative purposes of the Bureau of Land Management.

Remonumentation of Original Corner Point,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

(Remonumenting the corner established by W. H. Byars, 1874)

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, determined at record distance from the original bearing trees:

A sawed fir stump, 28 ins. diam., bears N. 2° W.,
74 lks. dist., with a healed blaze. (Record
bearing, North).

A fir, 48 ins. diam., bears S. 68° E., 9 lks. dist.,
with a healed blaze. (Record bearing, S. 65° E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in
the ground, with brass cap marked

$\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$
T 22 S R 9 W
1963

from which a new bearing tree,

A hemlock, 8 ins. diam., bears N. $46\frac{1}{2}$ ° W.,
129 lks. dist., marked $\frac{1}{4}$ S13 BT.