

# County Surveyor's Record, Douglas County, Oregon

T. 22 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

S. 65° E., 15 lks. dist., with scribe marks T23S R7W SC visible on opened blaze.

A sawed and decayed fir stump, 28 ins. diam., bears S. 42° W., 6 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

*FO. OK 9/92  
BY BECKLEY M 119-80*

S 1 | S 6  
R 8 W R 7 W  
T 23 S  
S C  
1964

from which a new bearing tree and a reference monument:

A fir, 20 ins. diam., bears S. 42° E., 109 lks. dist., mkd. T23S R7W S6 SC BT.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 20° W., 130 lks. dist., with brass cap mkd. T23S R8W S1 SC RM 1964 and an arrow pointing to the corner.

N. 89° 51' W., along the N. bdy. of sec. 1, on true line

Descend 80 ft. over NW. slope, through scattering timber and medium undergrowth.

3.20 Point for the closing cor. of Tps. 22 S., Rs. 7 and 8 W, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

C C  
T 22 S  
R 8 W R 7 W  
S 36 | S 31  
S 1  
T 23 S R 8 W  
1964

*FOOT  
MARK  
1964*

from which

A fir, 18 ins. diam., bears N. 47½° E., 170 lks. dist., mkd. T22S R7W S31 CC BT.

A fir, 11 ins. diam., bears N. 76½° W., 152 lks. dist., mkd. T22S R8W S36 CC BT.

Deposit broken brown glass at base of iron post.

Descend 110 ft. over NW. slope.

4.00 Paved road, 25 lks. wide, bears NE. and SW.

9.35 Branch, 3 lks. wide, course N. 20° W.; asc. 45 ft. over NE. slope.

10.45 Same paved road, 25 lks. wide, bears N. 31° W. and S. 31° E.

11.50 Top of ascent, slopes N.; desc. 35 ft. over gentle NW. slope.