

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the E. Bdy. of T. 22 S., R. 8 W.

CHAINS

T22S  
R8W R7W  
S24|S19  
S25|S30  
1963

from which new bearing trees:

A fir, 6 ins. diam., bears N.  $75\frac{3}{4}^\circ$  E., 56 lks. dist., mkd. T22S R7W S19 BT.

A fir, 9 ins. diam., bears S.  $10\frac{1}{4}^\circ$  E., 31 lks. dist., mkd. T22S R7W S30 BT.

A fir, 10 ins. diam., bears S.  $23\frac{1}{2}^\circ$  W.,  $53\frac{1}{2}$  lks. dist., mkd. T22S R8W S25 BT.

A fir, 5 ins. diam., bears N.  $78^\circ$  W.,  $36\frac{1}{2}$  lks. dist., mkd. T22S R8W S24 BT.

Cor. falls at W. edge of a skid road, 15 lks. wide, bears N.  $25^\circ$  W. and S.  $20^\circ$  E.

Land, mountainous.

Soil, sandy clay.

Timber, fir, hemlock, cedar, oak, maple, alder, and yew; undergrowth, vine maple, hazel, arrowwood, salmonberry, huckleberry, salal, poison oak, Oregon grape, and fern.

Dependent Resurvey of a Portion of the S. Bdy. of T. 21 S., R. 8 W.

(Restoring the surveys by William H. Byars in 1874 and 1881, resurveyed by Norman D. Price in 1945)

From the cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., 10 ins. above ground, firmly set, with brass cap marked

T21S R8W  
S32|S33  
T22S R8W  
1945

*FD OK  
Les Roberts  
M124-44  
2-10-97*

from which the bearing trees marked by Price:

A down fir, 38 ins. diam., bears N.  $45\frac{1}{2}^\circ$  E., 53 lks. dist., with a healed blaze.

A cedar, 14 ins. diam., bears N.  $70^\circ$  W., 55 lks. dist., with a healed blaze. (Record distance, 53 lks.)

and a new bearing tree,

A fir, 23 ins. diam., bears N.  $47^\circ$  E., 66 lks. dist., mkd. T21S R8W S33 BT.

S.  $89^\circ 19'$  W., along the S. bdy. of sec. 32, on true line.

Ascend 30 ft. over SE. slope, through heavy timber and dense undergrowth.

3.30 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.

7.75 Branch, 1 lk. wide, course S.; asc. 150 ft. over SE. slope.