

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the S. Bdy. of T. 21 S., R. 8 W.

CHAINS

from which

A fir, 45 ins. diam., bears S. $31\frac{1}{4}^\circ$ E., 556 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A fir, 44 ins. diam., bears S. 45° W., 340 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Descend 524 ft. over broken SW. slope.

34.50 Branch, 3 lks. wide, course N. 15° W.; asc. 250 ft. over precipitous E. slope.

39.16 The cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., 10 ins. above ground, firmly set, with brass cap marked

T21S R8W
S31 | S32

T22S R8W
S5
1945

from which the remaining bearing tree marked by Price,

A sawed fir stump, 38 ins. diam., bears N. $19\frac{1}{2}^\circ$ W., 182 lks. dist., with fragmentary scribe marks visible on burned face of blaze.

and new bearing trees:

A sawed fir stump, 40 ins. diam., bears N. 9° E., 186 lks. dist., mkd. T21S R8W S32 BT.

A sawed fir stump, 50 ins. diam., bears N. 71° W., 102 lks. dist., mkd. T21S R8W S31 BT.

Set a 7 ft. steel fence post, 2 ft. in the ground alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple and alder; undergrowth, hazel, vine maple, salmonberry, huckleberry, salal, poison oak, and fern.

S. $89^\circ 20'$ W., along the S. bdy. of sec. 31.

Ascend 60 ft. over E. slope, across old logged and burned area, through scattering snags and dense brush.

1.75 Spur, slopes N.; desc. 240 ft. over NW. slope.

13.15 Branch, 1 lk. wide, course N. 35° W.; asc. 10 ft. over NE. slope.

15.70 Spur, slopes N.; desc. 60 ft. over NW. slope.

18.28 The cor. of secs. 5 and 6, T. 22 S., R. 8 W., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, with brass cap marked

T21S R8W
S31

S6 | S5
T22S R8W
1945

from which the remaining original bearing tree,