

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS	
42.45	Branch, 2 lks. wide, course S. 15° E.; asc. 30 ft. over SE. slope.
44.75	Branch, 4 lks. wide, course S. 60° E.; asc. 250 ft. over NE. slope.
62.10	Spur, slopes SE.; dirt road, 15 lks. wide, bears NW. and SE.; desc. 30 ft. over SW. slope.
72.25	Ravine, drains S.; asc. 80 ft. over SE. slope.
75.20	Leave timber; enter open pasture land, edge bears N. and SW.
79.48	The cor. of secs. 25, 26, 35, and 36. Land, mountainous. Soil, sandy, rocky clay. Timber, oak, fir, hemlock, maple, and alder; undergrowth, vine maple, hazel, salmonberry, huckleberry, salal, arrowwood, poison oak, and fern.
	N. 3° 36' W., bet. secs. 25 and 26. Ascend 90 ft. over SE. slope, across open pasture land.
5.90	Dirt road, 15 lks. wide, bears N. 80° E. and W.
8.90	Top of ascent, slopes E.; desc. 30 ft. over NE. slope.
15.25	Bottom of descent, slopes E.; asc. 30 ft. along broken general E. slope.
30.65	Ridge, bears E. and W.; leave pasture; enter timber, edge bears E. and W.; desc. 150 ft. over NE. slope.
40.26	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, determined at record bearing and distance from the original bearing trees: A madrone, 18 ins. diam., bears S. 33° E., 85 lks. dist., with fragmentary scribe marks visible on opened blaze. A fir, 60 ins. diam., bears N. 29 $\frac{1}{2}$ ° W., 61 lks. dist., with no marks remaining on opened blaze. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S 26 S 25 T 22 S R 8 W 1964 </div> from which new bearing trees: A fir, 18 ins. diam., bears N. 80° E., 44 lks. dist., mkd. $\frac{1}{4}$ S25 BT. A chinquapin, 11 ins. diam., bears N. 80° W., 70 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
	N. 2° 14' E., beginning new measurement. Descend 245 ft. over general N. slope.