

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS	
18.50	Ravine, drains N. 65° W.; asc. 20 ft. over SW. slope.
22.05	Spur, slopes W.; desc. 90 ft. over NW. slope.
24.50	Branch, 3 lks. wide, course W.; asc. 60 ft. over SW. slope.
28.70	Spur, slopes N. 70° W.; desc. 110 ft. over NW. slope.
40.20	Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
 S 23 | S 24
 S 26 | S 25
 1964

*FD. 2/92
 R. Hoffine
 1114-47*
 from which

- A fir, 17 ins. diam., bears N. 25¼° E., 32 lks. dist., mkd. T22S R8W S24 BT.
- A fir, 8 ins. diam., bears S. 9½° E., 177 lks. dist., mkd. T22S R8W S25 BT.
- A hemlock, 40 ins. diam., bears S. 19½° W., 153 lks. dist., mkd. T22S R8W S26 BT.
- A fir, 32 ins. diam., bears N. 56½° W., 18 lks. dist., mkd. T22S R8W S23 BT.

From this point, the cor. of secs. 11, 12, 13, and 14, bears N. 0° 07' W., 160.70 chs. dist., remonumented in 1962 by the County Surveyor with an iron post, 1½ ins. diam., 6 ins. above ground, firmly set, with brass cap marked

COUNTY SURVEYORS OFFICE
 T 22 S
 S 11 | S 12
 S 14 | S 13
 R 8 W
 1962

from which the remaining original bearing trees:

- A burned fir stump, 60 ins. diam., bears S. 30½° W., 90 lks. dist., with no marks remaining.
- A fir snag, 65 ins. diam., bears N. 70° W., 24 lks. dist., with scribe marks S11 T22S R8W visible on opened blaze.

and bearing trees marked by the County Surveyor:

- A fir, 8 ins. diam., bears N. 52° E., 23 lks. dist., with scribe marks T22S R8W S12 CS BT visible on unhealed blaze.
- An alder, 15 ins. diam., bears S. 62° E., 50 lks. dist., with scribe marks T22S R8W S13 CS BT visible on unhealed blaze.
- A maple, 12 ins. diam., bears S. 87° W., 70 lks. dist., with scribe marks T22S R8W S14 CS BT visible on unhealed blaze.