

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

A down fir, 30 ins. diam., bears West, 31 lks. dist., with scribe marks 4 8 visible on opened blaze.

and trees marked by the County Surveyor in 1961:

A fir, 15 ins. diam., bears N. $19\frac{1}{2}^{\circ}$ E., 69 lks. dist., with scribe marks $\frac{1}{4}$ S27 CS BT visible on unhealed blaze.

A fir, 18 ins. diam., bears N. 38° W., $48\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S28 CS BT visible on unhealed blaze.

N. $6^{\circ} 45'$ W., beginning new measurement.

Ascend 70 ft. over SW. slope.

- 3.00 Top of ascent, slopes W.; desc. 120 ft. over NW. slope.
 9.10 Ravine, drains N. 67° W.; asc. 100 ft. over SW. slope.
 16.75 Spur, slopes N. 40° W.; desc. 90 ft. over NE. slope.
 20.65 Point for the N 1/16 sec. cor. of secs. 27 and 28.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

N 1/16
 S 28 | S 27
 1963

from which

A fir, 10 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ E., $18\frac{1}{2}$ lks. dist., mkd. N 1/16 S27 BT.

A fir, 14 ins. diam., bears N. $59\frac{1}{4}^{\circ}$ W., 32 lks. dist., mkd. N 1/16 S28 BT.

Descend 530 ft. over NE. slope.

- 40.90 Branch, 1 lk. wide, course N. 45° W.; asc. 5 ft. over SW. slope.
 41.30 The cor. of secs. 21, 22, 27, and 28, determined at record bearing and distance from the remaining original bearing tree,
 A decayed fir stump, 12 ins. diam., bears N. 68° E., 24 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked

FD OK, 1194, M120-49 A1⁶

T 22 S R 8 W
 S 21 | S 22
 S 28 | S 27
 1963

from which new bearing trees

A fir, 8 ins. diam., bears N. 84° E., 106 lks. dist., mkd. T22S R8W S22 BT.

A fir, 12 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., 144 lks. dist., mkd. T22S R8W S27 BT.