

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS 9.00	Paradise Creek, 35 lks. wide, course S. 30° W.; asc. 25 ft. over E. slope.
9.50	Enter field, edge bears N. 30° E. and S. 30° W.; thence across level land.
14.55	Leave field, edge bears N. 20° W. and S. 20° E.; asc. 170 ft. over SE. slope, through light timber and undergrowth.
15.30	Gravelled road, 25 lks. wide, bears N. and S. 10° E.
20.205	Point for the E 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked $E \frac{1}{16} \frac{S \ 3}{S \ 10}$ 1965 from which A fir, 18 ins. diam., bears N. 19½° W., 87 lks. dist., mkd. E 1/16 S3 BT. A fir, 6 ins. diam., bears S. 42° W., 7 lks. dist., mkd. E 1/16 S10 BT. Ascend 450 ft. over SE. slope.
23.30	Gravelled road, 40 lks. wide, bears N. 30° E. and S. 30° W.
40.41	Point for the ¼ sec. cor. of secs. 3 and 10 at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked FD. OK. 5/86 By ROBERTS C.S. 63/18 $\frac{1}{4} \frac{S \ 3}{S \ 10}$ T 22 S R 8 W 1965 from which A fir, 10 ins. diam., bears N. 43½° E., 78 lks. dist., mkd. ¼ S3 BT. A white fir, 12 ins. diam., bears S. 73° E., 143 lks. dist., mkd. ¼ S10 BT. Ascend 120 ft. over SE. slope.
51.60	Spur ridge, bears N. and S.; desc. 230 ft. over W. slope, changing to NW. slope.
60.615	Point for the W 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked $W \frac{1}{16} \frac{S \ 3}{S \ 10}$ 1965 from which