

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

A fir, 13 ins. diam., bears N. 54° E., 46 lks. dist., mkd. W $1/16$ S3 BT.

A fir, 38 ins. diam., bears S. 86° W., 84 lks. dist., mkd. W $1/16$ S10 BT.

Descend 180 ft. over NW. slope.

66.15 Creek, 2 lks. wide, course S. 60° W.; asc. 10 ft. over SE. slope.

67.75 Spur, slopes S. 40° W.; desc. 80 ft. over W. slope.

68.85 Creek, 3 lks. wide, course S.; asc. 180 ft. over E. slope.

80.82 The cor. of secs. 3, 4, 9, and 10, remonumented by the County Surveyor in 1962, with an iron post, $1\frac{1}{4}$ ins. diam., 6 ins. above ground, firmly set, with a brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S
S 4 | S 3
S 9 | S 10
R 8 W
1962

from which an original bearing tree,

A fir snag, 24 ins. diam., bears N. 62° E., 47 lks. dist., with fragmentary scribe marks visible on opened blaze.

and bearing trees marked by the County Surveyor:

A fir, 12 ins. diam., bears N. $76\frac{1}{2}^{\circ}$ E., 134 lks. dist., with scribe marks T22S R8W S3 CS BT visible on partly healed blaze.

A fir, 10 ins. diam., bears S. 73° E., 103 lks. dist., with scribe marks T22S R8W S10 CS BT visible on partly healed blaze.

A fir, 12 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ W., 43 lks. dist., with scribe marks T22S R8W S9 CS BT visible on partly healed blaze.

A fir, 23 ins. diam., bears N. 45° W., 86 lks. dist., with scribe marks T22S R8W S4 CS BT visible on partly healed blaze.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, and alder; undergrowth, poison oak, hazel, arrowwood, salmonberry, huckleberry, willow, vine maple, and fern.

From the point for the cor. of secs. 16, 17, 20, and 21, which is determined at proportionate distance; there is no remaining evidence of the original corner. (The departure of the line bet. secs. 17 and 20 is based on the random line reported by Byars.)

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., with top 28 ins. below surface of ground, with brass cap marked

T 22 S R 8 W
S 17 | S 16
S 20 | S 21
1963