

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

from which

An apple, 10 ins. diam., bears N. $86\frac{3}{4}^{\circ}$ E., 168 lks. dist., mkd. T22S R8W S16 BT.

A maple, 10 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ E., 145 lks. dist., mkd. T22S R8W S21 BT.

An oak, 15 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ W., 550 lks. dist., mkd. T22S R8W S20 BT.

No other suitable bearing tree available.

Deposit broken glass at base of iron post.

From this point the cor. of secs. 20, 21, 28, and 29, bears S. $0^{\circ} 20'$ W., 80.88 chs. dist., determined at record bearing and distance from the remaining original bearing tree,

A white oak, 30 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ E., 643 lks. dist., with no scribe marks visible on opened and decayed blaze. According to a signed statement furnished by Fred F. Riley, Sr., hereto appended, there were visible scribe marks on the blaze a few years ago. This tree is accepted as the best available evidence of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., with top 20 ins. below surface of ground, with brass cap marked

fd OK, 1194, M120-49	T 22 S R 8 W
At B	S 20 S 21
	S 29 S 28
	1963

from which a reference monument and new bearing trees:

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, at the corner of fences extending N. and W., for a reference monument, bears N. $51\frac{1}{4}^{\circ}$ E., 402 lks. dist., with brass cap mkd. T22S R8W S21 RM 1963 and an arrow pointing to the corner.

A fir, 9 ins. diam., bears S. $49\frac{3}{4}^{\circ}$ E., 536 lks. dist., mkd. T22S R8W S28 BT.

A maple, 36 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 332 lks. dist., mkd. T22S R8W S20 BT.

Corner falls in a cultivated field. Deposit 40 lbs. of assorted scrap iron at base of corner monument.

From the same point the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, bears S. $88^{\circ} 24'$ E., 39.36 chs. dist., determined at record bearing and distance from the remaining original bearing tree,

A white oak, 34 ins. diam., bears N. 84° E., 384 lks. dist., with no scribe marks visible on opened and decayed blaze. According to a signed statement furnished by Donald Agee, hereto appended, there were visible scribe marks on the blaze a few years ago. This tree is accepted as the best available evidence of the original corner.

At the corner point