

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

55.42

True point for the SW. cor. of Donation Land Claim No. 47, which falls in a creek 2 lks. wide, course S. 35° E., perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent; from which the trees mkd. by Frear:

An oak, 16 ins. diam., bears N. 71½° E., 81 lks. dist., with partial scribe marks visible on opened blaze.

An oak, 16 ins. diam., bears N. 82° E., 90 lks. dist., with healed blaze.

From this point a witness corner established by Fred Darby, County Surveyor, in 1962, bears East, 23 lks. dist., monumented with an iron post, 1½ ins. diam., 10 ins. above ground, firmly set, with brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S

W D L C

C 47 R 8 W

SW

15 ft. to cor.

1962

from which bearing trees mkd. by Darby:

A fir, 10 ins. diam., bears S. 74° E., 93 lks. dist., with scribe marks W C SW D L C CS 47 BT visible on open blaze.

A fir, 14 ins. diam., bears S. 78° W., 10½ lks. dist., with scribe marks WC SW D L C 47 CS BT visible on open blaze.

Ascend 56 ft. over SE. slope.

55.95 Woven wire fence, bears N. 50° W. and S. 50° E.

60.95 Spur, slopes E.; desc. 50 ft. over broken NE. slope.

66.95 Creek, 4 lks. wide, course S. 45° E.; asc. 240 ft. over SE. slope.

70.55 Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.

80.88 The cor. of secs. 8, 9, 16, and 17, remonumented and recorded by Fred Darby, County Surveyor, in 1962; monumented with an iron post, 1½ ins. diam., 10 ins. above ground, firmly set, with brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S R 8 W

S 8 S 9

S 17 S 16

1962

from which the original bearing trees:

A down fir, 72 ins. diam., bears N. 60° E., 5 lks. dist., with fragmentary scribe marks visible in bark.

A sawed fir stump, 26 ins. diam., bears S. 10° E., 39 lks. dist., with scribe marks 16 S22 R8W visible on rotted blaze.

A fir snag, 28 ins. diam., bears S. 56° W., 22 lks. dist., with partial scribe marks visible on opened blaze.