

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS 80.78	<p>The cor. of secs. 4, 5, 8, and 9, determined at record bearing and distance from the remaining original bearing trees:</p> <p style="margin-left: 40px;">A sawed and rotted fir stump, 52 ins. diam., bears N. 66° E., 79 lks. dist., with remnants of healed blaze visible.</p> <p style="margin-left: 40px;">A sawed and rotted fir stump, 48 ins. diam., bears S. 66° W., 131 lks. dist., with scribe marks T S8 R W T visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T 22 S R 8 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td colspan="2"></td> </tr> <tr> <td colspan="4" style="text-align: center;">1963</td> </tr> </table> </div> <p>from which new bearing trees:</p> <p style="margin-left: 40px;">A white fir, 16 ins. diam., bears S. 45° E., 119 lks. dist., mkd. T22S R8W S9 BT.</p> <p style="margin-left: 40px;">A dead fir, 10 ins. diam., bears N. 75° W., 85 lks. dist., mkd. T22S R8W S5 BT.</p> <p style="margin-left: 40px;">No other suitable bearing trees available.</p> <p style="margin-left: 40px;">Raise a mound of stone, 2 ft. base, 1 ft. high, W. of corner.</p> <p>Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir, hemlock, maple, oak, alder, and cedar; undergrowth, fern, hazel, vine maple, poison oak, and salal.</p>	T 22 S R 8 W				S 5	S 4			S 8	S 9			1963			
T 22 S R 8 W																	
S 5	S 4																
S 8	S 9																
1963																	
	<p>N. 5° 41' E., bet. secs. 4 and 5.</p> <p>Descend 150 ft. over N. slope, through scattering timber and dense undergrowth.</p>																
5.60	Skid road, 10 lks. wide, bears E. and W.																
6.40	Enter open field, edge bears E. and W.																
9.00	Left bank of Umpqua River, bears N. 55° E. and S. 55° W., course of river S. 60° W.																
17.18	Intersect NE. boundary of Donation Land Claim No. 49. Point falls in the Umpqua River; no monument set for closing corner.																
	<p>From this point, a corner of Donation Land Claim No. 49, on the left bank of the Umpqua River, bears S. 40° 44' E., 5.67 chs. dist., hereinafter described.</p>																
22.80	Right bank of Umpqua River, bears N. 70° E. and S. 60° W., asc. slightly over S. slope.																
22.93	Point for witness meander corner of secs. 4 and 5, on shoulder of highway.																
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap marked</p>																