


## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

T 22 S R 8 W



from which

A fir, 12 ins. diam., bears N.  $20\frac{1}{4}^{\circ}$  E., 216 lks. dist., mkd. X BT.

An oak, 15 ins. diam., bears N.  $62^{\circ}$  W., 225 lks. dist., mkd. X BT.

Deposit broken glass and set an iron pipe, 3 ft. long,  $\frac{3}{4}$  in. diam., alongside the iron post.

(This is the only practicable location for a monument on line in the vicinity of the corner.)

From this point, the witness meander cor. of the NE. bdy. of Claim No. 49, bears S.  $64^{\circ} 52'$  W., 4.32 chs. distant.

Ascend slightly over S. slope.

23.15 State Highway No. 38, 35 lks. wide, bears N.  $65^{\circ}$  E. and S.  $65^{\circ}$  W.

24.225 True point for the meander corner of secs. 4 and 5, established by Byars in 1881, at proportionate distance; there is no remaining evidence of the original corner. This point falls in a yard where it is impracticable to establish a permanent monument.

24.29 From this point the NE. cor. of a wood frame shed, 10.3 ft. by 8.3 ft., bears West, 16 lks. dist.; long side bears N.  $11^{\circ}$  W. and S.  $11^{\circ}$  E.

24.37 From this point the NW. cor. of a wood frame cabin, 18.8 ft. by 12.5 ft., bears East, 5 lks. dist.; long side bears N.  $77^{\circ}$  E. and S.  $77^{\circ}$  W.

Ascend 380 ft. over broken SW. slope.

38.00 The  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, perpetuated and recorded by James W. Byron in 1958, monumented with an iron post,  $1\frac{1}{2}$  ins. diam., 10 ins. above ground, firmly set, with brass cap marked

COUNTY SURVEYORS OFFICE

T 22 S R 8 W

 $\frac{1}{4}$  S 5 | S 4  
1958

from which the remaining original bearing tree,

A sawed fir stump, 26 ins. diam., bears S.  $1^{\circ}$  W., 191 lks. dist., with no marks remaining.

bearing trees mkd. by Byron:

A sawed fir stump, 26 ins. diam., bears S.  $5^{\circ}$  E., 103 lks. dist., with scribe marks BT visible on unhealed blaze.

A fir, 26 ins. diam., bears S.  $83^{\circ}$  W., 15 lks. dist., with scribe marks  $\frac{1}{4}$  S5 BT visible on unhealed blaze.

and a bearing tree mkd. by Milo E. Godfry, Deputy County Surveyor, in 1962,