

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22S., R. 8 W.

CHAINS

14.30

Leave pasture land, edge bears N. and S.; asc. 721 ft. over SE. slope, through old logged area.

38.93

Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \quad \frac{S \ 17}{S \ 20} \\ T \ 22 \ S \ R \ 8 \ W \\ 1963 \end{array}$$

from which

An oak, 9 ins. diam., bears N.  $42\frac{1}{2}^\circ$  W., 218 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

A fir, 10 ins. diam., bears S.  $82^\circ$  W., 257 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

Ascend 170 ft. over broken NE. slope.

50.90

Ridge, bears N.  $50^\circ$  W. and S.  $50^\circ$  E.; desc. 220 ft. over broken SW. slope.

59.15

Dirt road, 20 lks. wide, bears N. and S.

65.50

Dirt road, 20 lks. wide, bears N.  $25^\circ$  W. and S.  $25^\circ$  E.

77.86

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., 6 ins. above ground, firmly set, with brass cap marked

$$\begin{array}{r} T \ 22 \ S \ R \ 8 \ W \\ \frac{S \ 18 \ S \ 17}{S \ 19 \ S \ 20} \\ 1931 \end{array}$$

from which the remaining original bearing tree,

A rotted fir stump, 65 ins. diam., bears N.  $70^\circ$  W., 59 lks. dist., with healed blaze.

bearing trees mkd. by George F. Rigby in 1931:

A rotted fir stump, 36 ins. diam., bears N.  $11\frac{1}{2}^\circ$  E., 57 lks. dist., with no marks remaining.

A sawed fir stump, 30 ins. diam., bears S.  $50\frac{1}{2}^\circ$  E., 76 lks. dist., with healed blaze. (Record bearing, S.  $52\frac{1}{2}^\circ$  E.)

A fir, 38 ins. diam., bears S.  $16\frac{1}{4}^\circ$  W., 56 lks. dist., with healed blaze.

and bearing trees mkd. by Fred Darby, County Surveyor, in 1963:

A fir, 15 ins. diam., bears N.  $48\frac{1}{4}^\circ$  E., 70 lks. dist., with scribe marks T22S R8W S17 CS BT visible on unhealed blaze.

A fir, 8 ins. diam., bears S.  $71\frac{1}{2}^\circ$  E., 68 lks. dist., with scribe marks T22S R8W S20 CS BT visible on unhealed blaze.