

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 8 W.

CHAINS

68.55 Leave creek, bottom, course N. 55° W.; asc. 110 ft. over NE. slope.

76.95 Spur, slopes N.; desc. 110 ft. over broken NW. slope.

82.53 The cor. of secs. 7, 8, 17, and 18.

Land, mountainous.

Soil, sandy and rocky.

Timber, fir, hemlock, cedar, maple, oak, alder, madrone, and cascara; undergrowth, fern, salal, hazel, poison oak, bunch grass.

From the cor. of secs. 7, 8, 17, and 18.

N. 1° 18' E., bet. secs. 7 and 8.

Descend 140 ft. over NW. slope, through heavy timber and dense undergrowth.

10.00 Creek, 3 lks. wide, course S. 80° W.; asc. 50 ft. along W. slope.

11.20 Enter open field, edge bears E. and W.

14.00 Top of ascent, slopes W.; desc. 140 ft. over NW. slope.

31.75 Leave field, edge bears N. 55° W. and S. 55° E.

31.80 Dirt road, 15 lks. wide, bears N. 65° W. and S. 65° E.

35.95 Creek, 4 lks. wide, course N. 50° W.; asc. 50 ft. over SW. slope.

38.10 Spur, slopes NW.; desc. 80 ft. over NE. slope.

39.15 Creek, 3 lks. wide, course N. 65° W.; asc. 6 ft. over SW. slope.

39.47 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ S \ 7 \ | \ S \ 8 \\ T \ 22 \ S \ R \ 8 \ W \\ 1963 \end{array}$$

from which

A fir, 16 ins. diam., bears S.  $71\frac{1}{2}$  ° E., 46 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.An alder, 15 ins. diam., bears S. 27° W., 19 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

Descend 30 ft. over NW. slope.

41.40 Left bank of the Umpqua River, course S. 50° W.

52.05 Right bank of the Umpqua River; asc. 330 ft. over S. slope.

68.80 State Highway No. 38, 35 lks. wide, paved, bears N. 50° E. and S. 50° W.; begin steep ascent over S. slope.