

County Surveyor's Record, Douglas County, Oregon

Resurvey of Boundaries of Claim No. 54, T. 22 S., R. 8 W.

CHAINS
29.48

The SE. cor. of Claim No. 54, on the N. bdy. of Claim No. 55, determined at record bearing and distance from the remaining original bearing tree,

A black oak, 21 ins. diam., bears N. 18° E., 221 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
C 54 S 34
1964

from which new bearing trees:

A fir, 6 ins. diam., bears N. 15° E., 36 lks. dist., mkd. T22S R8W S34 BT.

A white oak, 35 ins. diam., bears N. 63° W., 8½ lks. dist., mkd. T22S R8W C54 BT.

S. 89° 31' W., on a blank line bet. Claims No. 54 and 55.

38.55

The interior cor. of Claim No. 54 and NW. cor. of Claim No. 55, determined at record bearing and distance from the original bearing trees:

A decayed oak crown, 14 ins. diam., bears N. 20° E., 80 lks. dist., with no marks remaining.

An oak, 25 ins. diam., bears S. 89° E., 228 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 8 W
S 34
C 54
C 55
1963

from which a new bearing tree,

An oak, 18 ins. diam., bears N. 6¾° W., 39 lks. dist., mkd. T22S R8W C54 BT.

Corner is located at a corner of fences extending S., E., and W.

South, on a blank line bet. Claims No. 54 and 55.

10.00

The cor. of Claim No. 54 on the W. bdy. of Claim No. 55, determined at record bearing and distance from the original bearing trees:

A sawed and decayed oak stump, 20 ins. diam., bears S. 85½° E., 492 lks. dist., with no marks remaining.

A sawed and decayed oak stump, 16 ins. diam., bears S. 79° E., 472 lks. dist., with no marks remaining.