

County Surveyor's Record, Douglas County, Oregon

Resurvey of Boundaries of Claim No. 54, T. 22 S., R. 8 W.

CHAINS


A cedar, 17 ins. diam., bears N. 48° E., 113 lks. dist., mkd. T22S R8W C54 BT.

A fir, 17 ins. diam., bears S. 74½° E., 79 lks. dist., mkd. T22S R8W S33 BT.

N. 0° 24' E., on a blank line along the W. bdy. of Claim No. 54.

20.53 Point for closing cor. at intersection with the line bet. secs. 28 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A fir, 14 ins. diam., bears N. 60° W., 61 lks. dist., mkd. T22S R8W S28 CC BT.

A fir, 17 ins. diam., bears S. 62½° W., 32 lks. dist., mkd. T22S R8W S33 CC BT.

From this point the cor. of secs. 27, 28, 33, and 34, bears S. 88° 29' E., 23.06 chs. dist.

39.86 The NW. cor. of Claim No. 54.

Subdivision of Sections, T. 22 S., R. 8 W.,
Willamette Meridian, Oregon

Subdivision of Section 5

From the ¼ sec. cor. of sec. 5 only, on the N. bdy. of the Tp.

S. 2° 17' W., on the N. and S. center line of sec. 5, marking and blazing the true line.

Descend 30 ft. over SW. slope, through scattering timber and dense undergrowth.

11.45 Bottom of descent, slopes W.; asc. 10 ft. over NW. slope.

16.65 Ridge, bears E. and W.; desc. 45 ft. over SW. slope.

17.20 Dirt road, 25 lks. wide, bears E. and W.

19.60 Point for closing cor. at intersection with the NW. bdy. of Claim No. 49.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

