

County Surveyor's Record, Douglas County, Oregon


Subdivision of Section 5, T. 22 S., R. 8 W.

CHAINS

Continue on a blank line, over patented land.

42.74 The center $\frac{1}{4}$ sec. cor. of sec. 5.

58.63 Point for closing cor., at intersection with the NW. bdy. of Claim No. 49.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked

No suitable bearing trees available. Set a 7 ft. steel fence post, 24 ins. in the ground, alongside the iron post.

From this point the closing cor. of the E. and W. center line of the NW $\frac{1}{4}$ of sec. 5, on the NW. bdy. of Claim No. 49, hereinafter described, bears N. $39^{\circ} 25'$ E., 25.34 chs. dist.


Descend 20 ft. over SW. slope, through scattering timber and dense undergrowth.

64.30 Creek, 1 lk. wide, course S. 10° E.; asc. 240 ft. over SE. slope.74.55 Spur ridge, bears N. 20° E. and S. 20° W.; desc. 50 ft. over broken W. slope.76.05 Skid road, 15 lks. wide, bears N. 35° E. and S. 35° W.82.78 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.From the N $\frac{1}{16}$ sec. cor. of secs. 5 and 6.S. $89^{\circ} 53'$ E., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 5.

Ascend 250 ft. over broken SW. slope, through scattering timber and dense undergrowth.

1.60 Dirt road, 25 lks. wide, bears N. 45° W. and S. 45° E.17.95 Ridge, bears N. 80° E. and S. 80° W.; desc. 120 ft. over broken SE. slope.36.90 Same dirt road, bears N. 50° E. and S. 50° W.

40.205 Point for closing cor., at intersection with the NW. bdy. of Claim No. 49.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

from which

A fir, 8 ins. diam., bears N. $87\frac{1}{2}^{\circ}$ W., 194 lks. dist., mkd. S5 CC BT.A fir, 6 ins. diam., bears S. 82° W., 203 lks. dist., mkd. S5 CC BT.