

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 25, T. 22 S., R. 8 W.

CHAINS	
5.50	Spur, slopes S. 50° W.; desc. 290 ft. over SE. slope.
39.85	Branch, 3 lks. wide, course N. 15° E.; asc. 4 ft. over E. slope.
39.93	The center $\frac{1}{4}$ sec. cor. of sec. 25. Ascend 142 ft. over NE. slope.
49.40	Leave timber; enter open land; edge bears N. 40° E. and S. 40° W.
71.20	Top of ascent, slopes N.; desc. 40 ft. over NW. slope.
79.40	Bottom of descent, slopes N.; asc. 20 ft. over NE. slope.
81.73	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Subdivision of Section 27

From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 4 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1962 resurvey.


N. 2° 41' W., on the N. and S. center line of sec. 27.

Ascend 210 ft. over general S. slope, through scattering timber and light undergrowth.

16.60	Graded dirt road, 20 lks. wide, bears N. 75° E. and S. 75° W.
-------	---

19.96	Point for the closing cor., at intersection with the N. bdy. of Claim No. 54.
-------	---

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A fir, 10 ins. diam., bears N. 47° E., 149 lks. dist., mkd. T22S R8W S27 CC BT.

A fir, 10 ins. diam., bears N. 28° W., 72 lks. dist., mkd. T22S R8W S27 CC BT.

From this point the NE. cor. of Claim No. 54, bears S. 89° 58' E., 28.80 chs. dist., heretofore described.

Ascend 10 ft. over S. slope, marking and blazing the true line.

21.80	Ridge, bears E. and W.; enter heavy timber and dense undergrowth; edge bears E. and W.; desc. 240 ft. over broken N. slope.
-------	---

40.27	Point for the center $\frac{1}{4}$ sec. cor. of sec. 27, at intersection with the E. and W. center line.
-------	--

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked