

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 27, T. 22 S., R. 8 W.

CHAINS	C $\frac{1}{4}$ S 27 1964
	from which
	A white fir, 8 ins. diam., bears N. 79° E., 47 lks. dist., mkd. C $\frac{1}{4}$ S27 BT.
	A white fir, 10 ins. diam., bears S. 47° E., 29 $\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S27 BT.
	Descend 170 ft. over N. slope.
50.20	Branch, 2 lks. wide, course NE.; asc. 40 ft. over S. slope.
56.25	Top of ascent, slopes E.; desc. 30 ft. over N. slope.
59.75	Branch, 1 lk. wide, course N. 60° E.; desc. slightly over NE. slope.
61.10	Point for the center N 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked
	C N 1/16   S 27 C 1964
	from which
	A white fir, 4 ins. diam., bears N. 26° E., 49 lks. dist., mkd. CN 1/16 S27 BT.
	A chinquapin, 9 ins. diam., bears N. 88° W., 13 lks. dist., mkd. CN 1/16 S27 BT.
	Descend 10 ft. over NE. slope.
63.25	Ravine, drains E.; asc. 40 ft. over SE. slope.
65.20	Top of ascent, slopes E.; desc. 90 ft. over broken NE. slope.
72.25	Ravine, drains E.; asc. 100 ft. over SE. slope.
78.00	Top of ascent, slopes E.; desc. 190 ft. over NE. slope.
81.93	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
	S. 89° 29' W., on the E. and W. center line of section 27.
	Ascend 40 ft. over SE. slope, through heavy timber and dense undergrowth.
6.05	Branch, 2 lks. wide, course SE.; asc. 470 ft. over broken SE. slope.
29.30	Ridge, bears N. and S. 30° W.; desc. 240 ft. over SW. slope.
38.40	Ravine, drains NW.; asc. 4 ft. along N. slope.
40.80	The center $\frac{1}{4}$ sec. cor. of sec. 27.
	Ascend 10 ft. along N. slope.