

# County Surveyor's Record, Douglas County, Oregon

## Subdivision of Section 27, T. 22 S., R. 8 W.

<p>CHAINS 42.35</p>	<p>Top of ascent, slopes N.; desc. 150 ft. over NW. slope.</p>
<p>47.40</p>	<p>Branch, 2 lks. wide, course N. 20° E., enter scattering timber; edge bears N. 20° E. and S. 20° W.; asc. 275 ft. over general E. slope.</p>
<p>59.93</p>	<p>Point for the center W 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{G} \text{---} \text{S } 27 \text{---} \text{C} \\ 1964 \end{array}</math> </div> <p>from which</p> <p style="margin-left: 40px;">A white fir, 10 ins. diam., bears S. 88¼° E., 43 lks. dist., mkd. CW 1/16 S27 BT.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 14° W., 73 lks. dist., mkd. CW 1/16 S27 BT.</p> <p>There is no suitable bearing tree available N. of line.</p> <p>Ascend 170 ft. over general E. slope.</p>
<p>65.20</p>	<p>Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.</p>
<p>66.55</p>	<p>Leave timber; enter open pasture; edge bears N. and S.</p>
<p>70.95</p>	<p>Well, with non-operative hand pump, bears North, 0.08 chs. distant.</p>
<p>76.60</p>	<p>Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.</p>
<p>77.75</p>	<p>Ridge, bears N. 15° W. and S. 15° E.; desc. 40 ft. over W. slope.</p>
<p>79.06</p>	<p>The ¼ sec. cor. of secs. 27 and 28.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 1° 29' W., on the N. and S. center line of the SW¼ of sec. 27.</p> <p>Descend 20 ft. along E. slope, through medium timber and light undergrowth.</p>
<p>3.20</p>	<p>Bottom of descent, slopes E.; enter open pasture land; edge bears E. and W.; asc. 60 ft. over S. slope.</p>
<p>7.30</p>	<p>Graded dirt road, 20 lks. wide, bears E. and W.</p>
<p>14.80</p>	<p>Ridge, bears N. 70° W. and S. 70° E.; enter timber, edge bears same as ridge; desc. 150 ft. over general N. slope.</p>
<p>19.94</p>	<p>Point for closing cor., at intersection with the N. bdy. of Claim No. 54.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{W} \\ \text{S } 27 \text{---}   \text{CC} \\ \text{W} \\ \text{C } 54 \\ 1964 \end{array}</math> </div> <p>from which</p>