

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 27, T. 22 S., R. 8 W.

CHAINS	
	<p>A fir, 12 ins. diam., bears N. 86° E., 43 lks. dist., mkd. T22S R8W S27 CC BT.</p> <p>A fir, 15 ins. diam., bears N. 57° W., 91 lks. dist., mkd. T22S R8W S27 CC BT.</p> <p>From this point the closing cor. of secs. 27 and 28, on the N. bdy. of Claim No. 54, bears N. 89° 58' W., 19.60 chs. dist., heretofore described.</p> <p>Descend 110 ft. over broken NE. slope.</p>
30.10	Ravine, drains E.; asc. 140 ft. over S. slope.
39.99	The center W 1/16 sec. cor. of sec. 27.
	<p>N. 4° 47' W., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 27.</p> <p>Ascend 70 ft. over S. slope, through heavy timber and dense undergrowth.</p>
8.95	Top of ascent, slopes E.; desc. 190 ft. over NE. slope.
17.90	Bottom of descent, slopes E.; asc. 15 ft. over S. slope.
20.74	Point for the NW 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">NW 1/16 S27 1964</p> <p>from which</p> <p>A white fir, 31 ins. diam., bears N. 77° W., 18 lks. dist., mkd. NW 1/16 S27 BT.</p> <p>A fir, 26 ins. diam., bears S. 38° E.; 66$\frac{1}{2}$ lks. dist., mkd. NW 1/16 S27 BT.</p> <p>Ascend 100 ft. over general S. slope.</p>
33.75	Top of ascent, slopes E.; desc. 170 ft. over NE. slope.
41.46	The W 1/16 sec. cor. of secs. 22 and 27.
	<p>From the center N 1/16 sec. cor. of sec. 27.</p> <p>S. 88° 55' W., on the E. and W. center line of the NW$\frac{1}{4}$ of sec. 27.</p> <p>Descend 15 ft. over W. slope, through heavy timber and dense undergrowth.</p>
7.65	Branch, 2 lks. wide, course N. 40° E.; asc. 210 ft. over E. slope.
19.87	The NW 1/16 sec. cor. of sec. 27.
	Ascend 170 ft. over E. slope changing to NE. slope.
31.30	Spur, slopes N. 5° E.; desc. 150 ft. over broken NW. slope.