

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 32, T. 22 S., R. 8 W.


CHAINS

Descend 241 ft. over NW. slope.

49.30 Sawyer Creek, 10 lks. wide, course N. 50° E.; asc. 120 ft. over broken SE. slope.

59.305 Point for the center W 1/16 sec. cor. of sec. 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A hemlock, 10 ins. diam., bears N. 47° W., 98 lks. dist., mkd. CW 1/16 S32 BT.

A fir, 15 ins. diam., bears S. 56° W., 28 lks. dist., mkd. CW 1/16 S32 BT.

Ascend 440 ft. over broken SE. slope.

76.40 Gravelled road, 20 lks. wide, bears N. 35° E. and S. 35° W.

78.79 The ¼ sec. cor. of secs. 31 and 32.

From the center E 1/16 sec. cor. of sec. 32.

N. 0° 29' E., on the N. and S. center line of the NE¼ of sec. 32.


Descend 130 ft. over broken NE. slope, through heavy timber and dense undergrowth.

8.45 Branch, 2 lks. wide, course N. 75° E.; asc. 50 ft. over SE. slope.

16.30 Top of ascent, slopes E.; desc. 30 ft. over NE. slope.

19.90 Point for the NE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NE¼ of sec. 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked



from which

A maple, 42 ins. diam., bears N. 35° E., 11 lks. dist., mkd. NE 1/16 S32 BT.

A hemlock, 12 ins. diam., bears S. 14° W., 45 lks. dist., mkd. NE 1/16 S32 BT.

Descend 130 ft. over broken NE. slope.

29.50 Branch, 10 lks. wide, course N. 40° W.; asc. 140 ft. over general SW. slope.

39.86 The E 1/16 sec. cor. of secs. 29 and 32, monumented with an iron post, 2½ ins. diam., 5 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1960 resurvey.