

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 32, T. 22 S., R. 8 W.

CHAINS	From the N 1/16 sec. cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., 6 ins. above ground, firmly set, with brass cap marked
	N 1/16 S 32 S 33 1962
	from which the 1962 bearing trees:
	A maple, 9 ins. diam., dead and down, bears N. 14° E., 87 lks. dist.
	A maple, 10 ins. diam., dead and down, bears N. 7½° W., 44 lks. dist.
	and new bearing trees:
	A maple, 10 ins. diam., bears N. 24° E., 95 lks. dist., mkd. N 1/16 S33 BT.
	A white fir, 13 ins. diam., bears S. 10° W., 58 lks. dist., mkd. N 1/16 S32 BT.
	N. 89° 43' W., on the E. and W. center line of the NE¼ of sec. 32.
	Descend 15 ft. over SW. slope, through heavy timber and dense undergrowth.
3.60	Bottom of descent, slopes S.; asc. 20 ft. over SE. slope.
8.60	Spur, slopes S. 30° E.; desc. 225 ft. over SW. slope.
16.50	Branch, 6 lks. wide, course N. 30° W.; asc. 100 ft. over broken NE. slope.
19.84	The NE 1/16 sec. cor. of sec. 32.
	Ascend 240 ft. over broken NE. slope.
32.10	Spur, slopes N. 10° E.; desc. 300 ft. over general W. slope.
39.66	The center N 1/16 sec. cor. of sec. 32.
	From the W 1/16 sec. cor. of sec. 32 only, on the S. bdy. of the Tp.
	N. 0° 56' E., on the N. and S. center line of the SW¼ of sec. 32.
	Ascend 100 ft. over SE. slope, through heavy timber and dense undergrowth.
8.85	Spur, slopes SE.; desc. 220 ft. over NE. slope.
18.00	Ravine, drains SE.; asc. 25 ft. over SE. slope.
19.30	Spur, slopes S. 75° E.; desc. 10 ft. over NE. slope.
20.09	Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SW¼ of sec. 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked