

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 32, T. 22 S., R. 8 W.

CHAINS	
	SW 1/16 S32 1964
	from which
	A fir, 30 ins. diam., bears N. 46° E., 14 lks. dist., mkd. SW 1/16 S32 BT.
	A fir, 25 ins. diam., bears S. 67° W., 39 lks. dist., mkd. SW 1/16 S32 BT.
	Descend 25 ft. over NE. slope.
23.55	Branch, 5 lks. wide, course S. 80° E.; asc. 60 ft. over SE. slope.
25.55	Spur, slopes SE.; desc. 160 ft. over NE. slope.
33.95	Branch, 5 lks. wide, course S. 30° E.; asc. 60 ft. over SE. slope.
36.00	Spur, slopes E.; desc. 20 ft. over NE. slope.
38.65	Ravine, drains E.; asc. 10 ft. over SE. slope.
40.23	The center W 1/16 sec. cor. of sec. 32.
From the center S 1/16 sec. cor. of sec. 32.	
	N. 89° 28' W., on the E. and W. center line of the SW ¹ / ₄ of sec. 32.
	Descend 410 ft. over general W. slope, through heavy timber and dense undergrowth.
11.30	Sawyer Creek, 15 lks. wide, course N.; asc. 155 ft. over NE. slope.
19.54	The SW 1/16 sec. cor. of sec. 32.
	Ascend 270 ft. over NE. slope.
28.40	Spur, slopes N.; desc. 40 ft. over NW. slope.
29.80	Ravine, drains N.; asc. 200 ft. over NE. slope.
38.60	Gravelled road, 20 lks. wide, bears N. 40° E. and S. 75° W.
39.12	The S 1/16 sec. cor. of secs. 31 and 32.
Subdivision of Section 33, T. 22 S., R. 8 W.	
	From the ¹ / ₄ sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, 2 ¹ / ₂ ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1962 resurvey.
	N. 0° 10' E., on the N. and S. center line of sec. 33.
	Descend 84 ft. over N. slope, across logged-over, brushy pasture land, recently replanted to fir timber.
3.85	Beaver pond, 30 lks. wide, in branch, 2 lks. wide, course S. 80° E.; asc. 340 ft. over general S. slope.
39.30	Ridge, bears N. 80° E. and W.; enter timber; edge bears same as ridge; desc. 30 ft. over N. slope.