

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 33, T. 22 S., R. 8 W.

CHAINS 40.20	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 33, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">C $\frac{1}{4}$ S33 1964</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 41° E., 50 lks. dist., mkd. C $\frac{1}{4}$ S33 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ W., 35 lks. dist., mkd. C $\frac{1}{4}$ S33 BT.</p> <p>Descend 400 ft. over N. slope, changing to NW. slope.</p>
54.70	Branch, 2 lks. wide, course N. 50° E. bending to N.; desc. 50 ft. along E. slope.
60.55	Branch, 2 lks. wide, course NE.; desc. 40 ft. over broken NE. slope.
68.20	Branch, 5 lks. wide, course E.; asc. 70 ft. over SE. slope.
70.90	Spur, slopes E.; desc. 110 ft. over broken NE. slope.
80.54	The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1962 resurvey.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record of the 1962 resurvey.</p> <p>N. $89^{\circ} 26'$ W., on the E. and W. center line of sec. 33.</p> <p>Ascend 10 ft. over SE. slope, along N. edge of open pasture land.</p>
1.00	Spur, slopes S. 10° W.; desc. 100 ft. over SW. slope.
6.00	Bottom of descent, slopes S.; asc. 70 ft. over SE. slope.
12.50	Spur, slopes S.; desc. 30 ft. along S. slope.
21.50	Bottom of descent, slopes S.; asc. 50 ft. over SE. slope, changing to E. slope.
38.00	Ridge, bears N. 70° E. and S. 80° W.; desc. 30 ft. over NW. slope.
39.85	The center $\frac{1}{4}$ sec. cor. of sec. 33.
	Descend 40 ft. over NW. slope.
42.60	Ravine, drains N.; asc. 90 ft. over NE. slope.
45.70	Ridge bears N. 65° W. and S. 70° E.; desc. 10 ft. along S. slope.
51.50	Bottom of descent, slopes S.; asc. 90 ft. over E. slope.
59.72	Point for the CW 1/16 sec. cor. of sec. 33.