

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 33, T. 22 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

W 1/16
C _____ C
S 33
1964

from which

A white fir, 8 ins. diam., bears N. 23° W., 25 lks. dist., mkd. CW 1/16 S33 BT.

A white fir, 20 ins. diam., bears S. 19° W., 24 lks. dist., mkd. CW 1/16 S33 BT.

Corner falls at corner of logged-over pasture land; edges bear S. and E.

Ascend 20 ft. over E. slope.

60.80 Ridge, bears N. 10° W. and S. 10° E.; desc. 360 ft. over W. slope.

72.60 Branch, 2 lks. wide, course NW.; asc. 80 ft. over NE. slope.

79.59 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

From the W 1/16 sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., 6 ins. above ground, firmly set, with brass cap marked

W 1/16
S 33
1962

from which the 1962 bearing trees:

A fir, 5 ins. diam., bears N. 72° E., 194 lks. dist., with healed blaze.

A white fir snag, 18 ins. diam., bears N. $67\frac{1}{2}^\circ$ W., 22 lks. dist., with scribe marks W 1/16 S33 BT visible on unhealed blaze.

and a new bearing tree,

A white fir, 18 ins. diam., bears N. 69° W., 78 lks. dist., mkd. W 1/16 S33 BT.

N. $0^\circ 26'$ E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 33.

Ascend 90 ft. over SE. slope, along W. edge of logged-over land, through dense brush.

8.85 Top of ascent, slopes E.; desc. 70 ft. over NE. slope.

11.50 Branch, 1 lk. wide, course S. 60° E.; asc. 230 ft. over SE. slope.

36.25 Spur, slopes SE.; desc. 10 ft. along E. slope.

40.13 The CW 1/16 sec. cor. of sec. 33.