

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Land Claim Corners, T. 22 S., R. 8 W., Will. Mer.

CHAINS

A cascara, 7 ins. diam., bears S. 51° E., 58 lks. dist., mkd. T22S R8W C51 BT.

A fir, 35 ins. diam., bears N. 59° W., 48 lks. dist., mkd. T22S R8W S17 BT.

Reset the steel bar alongside the iron post.

The SW. cor. of Claim No. 46, on the N. bdy. of Claim No. 51, determined at record bearing and distance from bearing trees mkd. by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent:

A sawed fir stump, 30 ins. diam., bears S. $79\frac{1}{4}^{\circ}$ W., 10 lks. dist., with fragmentary scribe marks visible on opened blaze.

A down fir, 28 ins. diam., bears N. 9° W., 5 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap marked

T 22 S R 8 W	
S 17	C 46
<hr style="width: 50%; margin: 0 auto;"/>	
C 51	
1963	

from which new bearing trees:

An oak, 12 ins. diam., bears N. 7° E., 114 lks. dist., mkd. T22S R8W C46 BT.

A fir, 25 ins. diam., bears S. 57° E., 41 lks. dist., mkd. T22S R8W C51 BT.

A fir, 10 ins. diam., bears N. 50° W., 78 lks. dist., mkd. T22S R8W S17 BT.

The NW. cor. of Claim No. 46, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., 8 ins. above ground, firmly set, from which the original bearing trees:

A sawed fir stump, 65 ins. diam., bears N. 67° E., 84 lks. dist., with a healed blaze.

A down fir, 40 ins. diam., bears S. 70° E., 152 lks. dist., with no marks remaining.

and bearing trees mkd. by Frear:

A down fir, 15 ins. diam., bears S. 57° E., 44 lks. dist., with a healed blaze.

A sawed fir stump, 24 ins. diam., bears S. 4° E., 34 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked