

19734 County Surveyor's Record, Douglas County, Oregon

Remonumentation of Land Claim Corners, T. 22 S., R. 8 W., Will. Mer.

CHAINS

T 22 S R 8 W  
S 17 | C 46  
1963

from which new bearing trees:

A fir, 22 ins. diam., bears S. 15° E., 68 lks. dist., mkd. T22S R8W C46 BT.

A fir, 9 ins. diam., bears N. 41° W., 59 lks. dist., mkd. T22S R8W S17 BT.

Reset the iron pipe alongside the iron post.

The interior cor. on the W. bdy. of Claim No. 47, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent; monumented with an iron pipe, 1½ ins. diam., 4 ins. above ground, firmly set, from which bearing trees mkd. by Frear:

A dead fir, 40 ins. diam., bears N. 54¼° E., 67 lks. dist., with a healed blaze.

A fir, 30 ins. diam., bears N. 79½° W., 28½ lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap marked

T 22 S R 8 W  
S 9 |  
C 47  
1963

from which a new bearing tree,

A fir, 7 ins. diam., bears S. 23½° W., 42 lks. dist., mkd. T22S R8W C47 BT.

Reset the iron pipe alongside the iron post.

The NW. cor. of Claim No. 47, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, monumented with an iron pipe, 1½ ins. diam., 8 ins. above ground, firmly set, from which the original bearing trees:

A sawed fir stump, 50 ins. diam., bears S. 7° E., 105 lks. dist., with a healed blaze.

A forked fir, 45 ins. diam., bears S. 75° W., 18 lks. dist., with a healed blaze. (Record bearing, S. 60° W.)

and a bearing tree mkd. by Frear,

A fir, 30 ins. diam., bears N. 40° W., 15 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked