

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Land Claim Corners, T. 22 S., R. 8 W., Will. Mer.

CHAINS

T 22 S R 8 W

$$\begin{array}{c} \text{S } 9 \text{ | C } 47 \\ \hline 1963 \end{array}$$

from which a new bearing tree,

A fir, 9 ins. diam., bears S.  $77\frac{1}{2}^{\circ}$  E., 74 lks. dist., mkd. T22S R8W C47 BT.

Reset the iron pipe alongside the iron post.

The SW. cor. of Claim No. 57, on the N. bdy. of Claim No. 47, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent; monumented with an iron pipe,  $1\frac{1}{2}$  ins. diam., 8 ins. above ground, firmly set, from which bearing trees mkd. by Frear:

A rotted fir stump, 14 ins. diam., bears N.  $14^{\circ}$  W., 31 lks. dist., with no marks remaining.

A down and rotted oak, 5 ins. diam., bears S.  $83^{\circ}$  W., 27 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T } 22 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 9 \text{ | C } 57 \\ \hline \text{C } 47 \\ 1963 \end{array}$$

from which new bearing trees:

A maple, 10 ins. diam., bears N.  $71^{\circ}$  E., 39 lks. dist., mkd. T22S R8W C57 BT.

A fir, 8 ins. diam., bears S.  $5^{\circ}$  E., 56 lks. dist., mkd. T22S R8W C47 BT.

A fir, 10 ins. diam., bears N.  $22^{\circ}$  W., 24 lks. dist., mkd. T22S R8W S9 BT.

Reset the iron pipe alongside the iron post.

The exterior cor. on the W. bdy. of Claim No. 57, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent, monumented with an iron pipe,  $1\frac{1}{2}$  ins. diam., 8 ins. above ground, firmly set, from which bearing trees mkd. by Frear:

A down fir, 65 ins. diam., bears N.  $18^{\circ}$  E., 125 lks. dist., with a healed blaze.

A down fir, 24 ins. diam., bears S.  $24\frac{1}{2}^{\circ}$  E., 12 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked