

## County Surveyor's Record, Douglas County, Oregon

Remonumentation of Land Claim Corners, T. 22 S., R. 8 W., Will. Mer.

CHAINS

T 22 S R 8 W

$$\begin{array}{c} \text{S } 9 \text{ | C } 57 \\ \hline 1963 \end{array}$$

from which new bearing trees:

A fir, 9 ins. diam., bears N.  $41\frac{1}{2}^{\circ}$  E., 57 lks.  
dist., mkd. T22S R8W S9 BT.

A fir, 18 ins. diam., bears S.  $39^{\circ}$  E., 78 lks.  
dist., mkd. T22S R8W C57 BT.

Reset the iron pipe alongside the iron post.

The interior cor. on the W. bdy. of Claim No. 57, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1917, when the original bearing trees were existent, monumented with an iron pipe, 18 ins. long,  $1\frac{1}{2}$  ins. diam., 10 ins. above ground, loosely set, from which bearing trees mkd. by Frear:

A down fir, 16 ins. diam., bears S.  $16^{\circ}$  E., 13 lks.  
dist., with fragmentary scribe marks visible on  
opened blaze.

A down and rotted fir, 12 ins. diam., bears  
S.  $37\frac{3}{4}^{\circ}$  W.,  $12\frac{1}{2}$  lks. dist., with a healed blaze.

At the corner point

Set an iron post, 14 ins. long, 1 in. diam., 8 ins. in  
drill hole in solid rock, with brass cap marked

$$\begin{array}{c} \text{T 22 S R 8 W} \\ \text{S } 9 \text{ | C } 57 \\ \hline 1963 \end{array}$$

from which new bearing trees:

A fir, 9 ins. diam., bears S.  $13\frac{1}{2}^{\circ}$  W., 108 lks.  
dist., mkd. T22S R8W C57 BT.

A fir, 18 ins. diam., bears N.  $44^{\circ}$  W., 55 lks.  
dist., mkd. T22S R8W S9 BT.

Deposit the iron pipe alongside the iron post.

The NW. cor. of Claim No. 57, on the S. bdy. of Claim  
No. 49, perpetuated and recorded by F. C. Frear,  
Deputy County Surveyor, in 1917, when the original  
bearing trees were existent, monumented with an iron  
pipe,  $1\frac{1}{2}$  ins. diam., 10 ins. above ground, firmly set,  
from which bearing trees mkd. by Frear:

A dogwood snag, 9 ins. diam., bears S.  $16^{\circ}$  E.,  
27 lks. dist., with fragmentary scribe marks  
visible on decayed blaze.

A decayed fir stump, bears N.  $67\frac{1}{4}^{\circ}$  W., 96 lks.  
dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap marked