

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 8 W.

CHAINS

A chinquapin, 8 ins. diam., bears N. 49° E., 39½ lks. dist., with scribe marks T25S R7W S30 BT visible on partially healed double blaze.

A fir, 10 ins. diam., bears S. 75° E., 16 lks. dist., with double healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

*FO. OK
6/9* BY DEC 2007
M 119-33*

T 25 S
R 8 W R 7 W
S 25 | S 30
S 36 | S 31
1964

From which new bearing trees

A white fir, 10 ins. diam., bears N. 74° E., 45 lks. dist., mkd. T25S R7W S30 BT.

A fir, 13 ins. diam., bears N. 27° W., 43 lks. dist., mkd. T25S R8W S25 BT.

Reset iron pipe alongside the iron post.

N. 0° 10' E., bet. secs. 25 and 30, marking and blazing the true line.

Descend 15 ft. over NE. slope, along the W. edge of logged area, through heavy timber and dense undergrowth.

1.00 Ravine, drains S. 60° E., asc. 365 ft. over SE. slope.

8.00 Spur, slopes S. 60° E.; desc. 35 ft. over NE slope.

10.70 Bottom of descent, slopes E.; asc. 180 ft. over precipitous SE slope.

16.00 Top of rock bluff, 40 ft. high, bears N. 30° E. and S. 30° W.; asc. 200 ft. over SE. slope.

21.80 Spur, slopes S. 70° E.; desc. 520 ft. over broken NE. slope.

33.00 Ravine, drains S. 70° E.; desc. 520 ft. over broken NE. slope.

43.40 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 1 ft. base to top, with brass cap mkd.

T 25 S
R 8 W ¼ R 7 W
S 25 | S 30
1964

from which

A fir, 8 ins. diam., bears N. 76° E., 11 lks. dist., mkd. ¼ S30 BT.