

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. B dy., T. 25 S., R. 8 W.

CHAINS

Ascent 290 ft. over SW. slope.

51.70 Spur, slopes S. 40. E.; desc. 345 ft. over NE. slope.

60.00 Head of ravine, drains S. 80° E.; asc. 290 ft. over SE. slope.

65.75 Point for the N 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16	
S 25	S 30
1964	

from which

A fir 19 ins. diam., bears N. 33. E., 29 lks. dist., mkd. N 1/16 S30 BT.

A fir, 12 ins. diam., bears S. 68° W., 37 lks. dist., mkd. N 1/16 S25 BT.

Ascend 135 ft. over SE. slope.

71.00 Top of ascent, slopes E.; desc. 30 ft. over NE. slope.

74.00 Ravine, drains S. 60° E.; asc. 240 ft. over SE. slope.

79.75 Ridge, dividing Hubbard Creek and Cougar Creek drainages, bears N. 60° E. and S. 80° W.; desc. 305 ft. over NW. slope.

80.00 Dirt road, 15 lks. wide, bears N. 60° E. and S. 80° W.

88.10 Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 25 S	
R 8 W	R 7 W
S 24	S 19
S 25	S 30
1964	

Handwritten notes: R 8 W R 7 W S 24 S 19 S 25 S 30 7-83 M 94-3

from which

A fir, 23 ins. diam., bears N. 48½° E., 32 lks. dist., mkd. T25S R7W S19 BT.

A fir, 23 ins. diam., bears S. 18¼° E., 45 lks. dist., mkd. T25S R7W S30 BT.

A fir, 19 ins. diam., bears S. 47½° W., 30 lks. dist., mkd. T25S R8W S25 BT.

A fir, 16 ins. diam., bears N. 82½° W., 37 lks. dist., mkd. T25S R8W S24 BT.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, white fir, madrone, alder, dogwood, yew, oak, and maple; undergrowth, vine maple, salal, ocean spray, hazel, Oregon grape, poison oak, manzanita, Rhododendron, huckleberry and blackberry.